



Concrete grey



Slate grey



Black



Natural red



Mocha

## New surfaces for paving slabs with StoneColor®

Over time your terrace, paving slabs and block pavements get old, looking dull and worn from water, frost, moss, algae and dirt. Now there is no need to go to the expense of replacing your patio or driveway, simply paint them with StoneColor®. StoneColor® is a special kind of surface treatment that is easily applied with a long-haired rya roller, a spray gun or a paint brush. StoneColor® provides a protective coating - which keeps the stones looking fresh for years after, while repelling water, oil and dirt.

StoneColor® is a product that was developed on the basis of the latest nanotechnology. It protects the surface area of all mineral surfaces such as paving stones from dirt, oil and water and thanks to its excellent wear resistance and general hardness, offers years of protection against weathering.

Further information and suggestions at [www.stonecolor.dk](http://www.stonecolor.dk)



### USAGE:

StoneColor® was specially developed for the surface treatment outdoors for absorbent and porous surfaces such as paving slabs and block pavements made of cement, concrete and lime sandstone.

Apply StoneColor® after thoroughly cleaning the surfaces of grease, dirt, dust etc. with StoneCleaner, as well as a high-pressure cleaner, to ensure the surface is free of dust, dirt and grease. Once the surface is dry, we recommend that once again, using a brush or vacuum cleaner, the final remaining particles of dirt are removed. This is the only way to guarantee optimal binding between StoneColor® and the surface to be coated and will achieve the best result.

### TECHNICAL DATA:

**Product:** StoneColor® **Use:** Coating, protection and impregnation of mineral surfaces outdoors. **Speciality chemicals:** Based on nanotechnological bonds with synthetic resins and UV-resistant pigments. **Basis:** Water-based, non-diluted or, depending on the use, dilute with water up to 10%. **Characteristics:** Strong adhesion, extremely long-lasting, resistant to oil, water and chemicals. UV-resistant for outdoor use. **Drying time:** Approx. 60 minutes at 20° C and with 60 % rel. humidity. **Application:** Via paintbrush, paint roller or spray gun. **Coverage:** 1 litre suffices for approx. 3 to 5 m<sup>2</sup>, depending on the state of the surface and application method. **Cleaning:** Rinse the tools used thoroughly in clear, tepid water. **Storage:** In a dry and frost-free place, out of reach of children. When correctly used, 5 year guarantee against flaking of concrete.

**Note:** always test the product on a portion of the surface to be treated, to check the tolerance. Must be stirred before and during use.

# GIVE YOUR PAVING SLABS A NEW LOOK QUICKLY & EASILY

## WITH NANOTECHNOLOGY



- RENEW YOUR PAVING SLABS
- NANOTECHNOLOGY
- LONG-LASTING
- EASY TO APPLY
- INHIBITS THE GROWTH OF MOSS AND ALGAE

\*Up to 5 years durability

## STONE AND TILE COATING



[www.stonecolor.dk](http://www.stonecolor.dk)

developed and produced by  
Nowocoat Industrial A/S  
[www.stonecolor.dk](http://www.stonecolor.dk)



# StoneColor®

## Stone and tile coating

For absorbent and porous cement and concrete surfaces

- Environmentally friendly and renewable
- Stay clean effect
- Lasts for many years
- Inhibits the growth of moss and algae
- Reinforces treated surfaces
- Water-based

**1** Clean with  
**StoneCleaner™**

**2** Coat with  
**StoneColor®**

**3** Lie back and  
enjoy the result

 StoneColor®



Coated with StoneColor® – Slate grey